



## Lexmark C2335

Exceptional performance, secure and sustainable



## Lexmark C2335

With exceptional performance and secure design, the C2335 printer delivers enhanced productivity, up to 35 ppm\* on letter paper and toner yields up to 20,000 pages mono\*\*, and up to 11,700 pages color\*\*. Engineered for long life with environmental certifications and advanced power management, this efficient model has high sustainability. Fast time to first print, superior print quality and easy-to-use touch screen.

### Secure by design

Lexmark expertise helps customers protect their data, their device and their network. Our security ecosystem is designed to overcome the most complex data challenges. And now we've added the Trusted Platform Module (TPM)\*\*\*, which includes on-board authentication, system integrity checks, and cryptographic capabilities to create a unique digital system fingerprint. TPM meets stringent industry and US government security standards including Common Criteria and Federal Information Processing Standard (FIPS).

### Proprietary technology

We own core technology across hardware, firmware, services, and solutions, creating seamless connections designed to reduce the risk of security gaps between your document, your device and your network. Our expertise is our customer's benefit.

### Sustainability

With certifications in Energy Star®, Blue Angel, RoHS, EPEAT® Silver. Models are sustainable for today and beyond. Lexmark is an industry leader of recycled content with products using at least 35% PCR content and continual focus on improvement. This line is also engineered for Long Life and designed to last and reduce waste.

### Intelligent Design

Every touch point is designed to withstand high usage while meeting accessibility standards. Steel frames support the device and provide durability to help ensure consistent long-term performance. Products are designed for long service life with long-life components and are easily serviced with few tools.



### Manageability

These IoT-ready devices can be remotely managed, including setup, configuration, consumables management, and diagnostics. Wireless capability gives freedom of access and remote firmware updates make it easy to upgrade to the latest apps and security features. Our mobile printing app makes it easier to monitor and manage your print jobs from remote locations, all from the touch of your phone.

### Ongoing professional product support


From easy installation through a lifetime of high volumes of pages, you'll find our devices easy to use and intuitive. From instructional and on-product support videos to simple color-coded guidance for maintenance tasks like changing toner, make our device experience world-class.

\* Print speeds measured in accordance with ISO/IEC 24734 (ESAT). For more information see: [www.lexmark.com/ISOspeeds](http://www.lexmark.com/ISOspeeds).

\*\* Average yield based on approximately 5% print coverage. In demonstration of circular economy principles, genuine Lexmark supplies with Unison™ Toner may contain components recovered from the Lexmark Cartridge Collection Program (LCCP). Lexmark Return Program cartridges are subject to the terms and conditions of the Lexmark Return Program. See [lexmark.com/returnprogram](http://lexmark.com/returnprogram) for more information. Regular cartridges without the terms and conditions of the Lexmark Return Program are available on [lexmark.com](http://lexmark.com) or through Lexmark Channel Partners.

\*\*\* The Trusted Platform Module (TPM) is not available in some countries.

# Lexmark C2335



- 1 **Printer with 2.8-inch (7.2 cm) touch screen**  
12.50 x 17.90 x 16.60 in.  
318.30 x 455 x 422.50 mm
- 2 **170-Sheet output bin**  
Dimensions included as part of base model
- 3 **Single sheet multipurpose feeder**  
Dimensions included as part of base model
- 4 **250-Sheet tray**  
Dimensions included as part of base model
- 5 **650-Sheet Duo Tray**  
5.2 x 16.7 x 16.4 in.  
132.1 x 424.2 x 416.6 mm

- 6 **550-Sheet Tray**  
5.2 x 16.7 x 16.4 in.  
132.1 x 424.2 x 416.6 mm
- 7 **550-Sheet Tray**  
5.2 x 16.7 x 16.4 in.  
132.1 x 424.2 x 416.6 mm
- 8 **Adjustable Stand**  
20.5 x 25.7 x 24.6 in.  
521 x 653 x 625 mm
- 9 **Swivel Cabinet**  
10.4 x 18.7 x 23.6 in.  
263 x 476 x 600 mm



<b>P/N</b> 50M0160	<b>Hardware</b> Lexmark C2335
<b>P/N</b> 24B7537	<b>Supplies</b> Lexmark C2335, XC2335 Cyan 11.7K Toner Cartridge
24B7538	Lexmark C2335, XC2335 Magenta 11.7K Toner Cartridge
24B7539	Lexmark C2335, XC2335 Yellow 11.7K Toner Cartridge
24B7540	Lexmark C2335, XC2335 Black 20K Toner Cartridge
75M0W00	Lexmark CS531, 632, 639, CX532, 635, C2335, XC2335 30K Waste Toner Bottle
75M0ZK0	Lexmark CS531, 632, 639, CX532, 635, C2335, XC2335 Black Return Program 150K Imaging Kit
75M0ZV0	Lexmark CS531, 632, 639, CX532, 635, C2335, XC2335 4-Color Return Program 150K Imaging Kit
<b>P/N</b> 50M7550 50M7650	<b>Paper Handling</b> 550-Sheet Tray 650-Sheet Duo Tray
<b>P/N</b> 57X9528	<b>Memory Options</b> Intelligent Storage Device (ISD)
<b>P/N</b> 57X0300 57X0301	<b>Application Solutions</b> Contact Authentication Device Contactless Authentication Device
82S1203 82S1204	IPDS License Bar Code License
<b>P/N</b> 1021294 SPD0001	<b>Connectivity</b> USB Cable (2-meter) Surge Protective Device, 110-120V
<b>P/N</b> 3073173 40C2300	<b>Furniture</b> Swivel Cabinet Adjustable Stand

Product Specifications		Lexmark C2335
<b>Printing</b>		
Display	2.8 inch (7.2 cm) Color touch screen	
Print Speed	Up to: Black: 35 ppm <sup>1</sup> (Letter) / Color: 35 ppm <sup>1</sup> (Letter)	
Time to First Page	As fast as: Black: 7.1 seconds / Color: 7.6 seconds	
Print Resolution	Black: 1200 x 1200 dpi, 4800 Color Quality / Color: 4800 Color Quality, 1200 x 1200 dpi	
Memory	Standard: 1024 MB / Maximum: 1024 MB	
Hard Disk	Intelligent Storage Drive (optional); Magnetic Hard Disk (optional)	
Recommended Monthly Page Volume	1,500 - 10,000 pages <sup>2</sup>	
Maximum Monthly Duty Cycle	Up to: 100,000 pages per month <sup>3</sup>	
<b>Supplies<sup>4</sup></b>		
Laser Cartridge Yields	up to: 20,000 <sup>5</sup> -page Black Cartridge / up to: 11,700 <sup>5</sup> -page Color (CMY) Cartridges	
Cartridge(s) Shipping with Product	3,000 <sup>5</sup> -page Black Return Program Toner Cartridge <sup>5</sup> , 2,000 <sup>5</sup> -page Color (CMY) Return Program Toner Cartridges <sup>5</sup>	
<b>Paper Handling</b>		
Included Paper Handling	170-Sheet Output Bin, Integrated Duplex, Single sheet multipurpose feeder, 250-Sheet Tray	
Optional Paper Handling	650-Sheet Duo Tray, 550-Sheet Tray	
Paper Input Capacity	Up to: Standard: 251 pages 20 lb or 75 gsm bond / Maximum: 2001 pages 20 lb or 75 gsm bond	
Paper Output Capacity	Up to: Standard: 170 pages 20 lb or 75 gsm bond / Maximum: 170 pages 20 lb or 75 gsm bond	
Media Types Supported	Vinyl Labels, Paper Labels, Card Stock, Plain Paper, Envelopes, Refer to the Card Stock & Label Guide.	
Media Sizes Supported	A6, Oficio, 7 3/4 Envelope, 9 Envelope, JIS-B5, A4, Legal, A5, Hagaki Card, Letter, B5 Envelope, Statement, C5 Envelope, Executive, Universal, DL Envelope, Folio, 10 Envelope	
<b>General Information<sup>6</sup></b>		
Standard Ports	Gigabit Ethernet (10/100/1000), Front USB 2.0 Specification Hi-Speed Certified port (Type A), Rear USB 2.0 Specification Hi-Speed Certified Port (Type A), 802.11a/b/g/n/ac + Apple iBeacon, USB 2.0 Specification Hi-Speed Certified (Type B)	
Noise Level	Operating: 51 dBA (Print)	
Specified Operating Environment	Altitude: 0 - 2900 Meters (9,500 Feet) / Humidity: 15 to 80% Relative Humidity / Temperature: 10 to 32.2°C (50 to 90°F)	
Limited Warranty	See Statement of Limited Warranty: 1-Year Onsite Service, Next Business Day	
Size / Weight	H x W x D: 12.50 x 17.90 x 16.60 in. / 45.31 lb.	
ENERGY STAR Typical Electricity Consumption	TEC: 0.46 kilowatt-hours per week	

All information is subject to change without notice. Lexmark is not liable for any errors or omissions.

<sup>1</sup> Print and copy speeds measured in accordance with ISO/IEC 24734 and ISO/IEC 24735 respectively (ESAT). For more information see: [www.lexmark.com/ISOspeeds](http://www.lexmark.com/ISOspeeds).

<sup>2</sup> "Recommended Monthly Page Volume" is a range of pages that helps customers evaluate Lexmark's product offerings based on the average number of pages customers plan to print on the device each month. Lexmark recommends that the number of pages per month be within the stated range for optimum device performance, based on factors including: supplies replacement intervals, paper loading intervals, speed, and typical customer usage. <sup>3</sup> "Maximum Monthly Duty Cycle" is defined as the maximum number of pages a device could deliver in a month using a multishift operation. This metric provides a comparison of robustness in relation to other Lexmark printers and MFPs. <sup>4</sup> Product functions only with replacement cartridges designed for use in a specific geographical region. See [www.lexmark.com/regions](http://www.lexmark.com/regions) for more details. <sup>5</sup> Average yield based on approximately 5% print coverage.

<sup>6</sup> Printers are sold subject to certain license/agreement conditions. See [www.lexmark.com/printerlicense](http://www.lexmark.com/printerlicense) for details.

© 2023 Lexmark. All rights reserved.

Lexmark, the Lexmark logo and Unison are trademarks of Lexmark International, Inc., registered in the United States and/or other countries.

Apple and AirPrint are trademarks of Apple Inc., registered in the U.S. and other countries and regions. MOPRIA®, the Mopria® Logo and the Mopria® Alliance™ logos are registered and/or unregistered trademarks and service marks of Mopria Alliance, Inc. in the United States and other countries. Unauthorized use is strictly prohibited. ENERGY STAR and the ENERGY STAR mark are registered trademarks owned by the U.S. Environmental Protection Agency. EPEAT® is a trademark of the Green Electronics Council in the United States and other countries. All other trademarks are the property of their respective owners.

This product includes software developed by the OpenSSL Project for use in the Open SSL Toolkit (<http://www.openssl.org/>).

